

CLIP HYPALON

Light weight and very flexible Hypalon® ducting

- Good Temperature Resistance
- Chemical Resistance

MEDIUM



PROPERTIES



Structure:

Hypalon® coated polyester fabric / external: black, internal: green

Characteristics:

Good temperature, UV and ozone resistance, excellent chemical resistance, outer wear strip, flame retardant and excellent axial compressibility, good mechanical strength

Applications:

Suction of hot or cold fumes, gases or dust in all fields of industry

Temperature range:

-40°C up to +175°C

Colour:

external: black, internal: green

Specials:

Clip Vinyl (80°C)
Clip Viton (210°C)
Clip PTFE (& EL) (250°C)
Clip Hypalon T EL (175°C)
Clip Silicone (300°C)
Clip Aramid (300°C)
Clip HT 450°C
Clip HT 650°C
Clip HT 1100°C

I.D. Ø mm	O.D. Ø mm	Wall thickness mm	r (mind.) mm	Weight approx. kg/m	Vacuum bar	Pressure bar	Part no.
50	-	0,40	30	0,400	400	0,85	5071050000
60	-	0,40	36	0,480	280	0,78	5071060000
76	-	0,40	45	0,600	170	0,60	5071076000

I.D. Ø mm	O.D. Ø mm	Wall thickness mm	r (mind.) mm	Weight approx. kg/m	Vacuum bar	Pressure bar	Part no.
80	-	0,40	48	0,620	160	0,58	5071080000
102	-	0,40	60	0,650	100	0,50	5071102000
110	-	0,40	66	0,700	80	0,48	5071110000
120	-	0,40	72	0,720	60	0,35	5071120000
127	-	0,40	75	0,800	60	0,32	5071127000
152	-	0,40	90	0,900	40	0,22	5071152000
160	-	0,40	96	0,940	40	0,21	5071160000
180	-	0,40	108	1,050	30	0,17	5071180000
203	-	0,40	120	1,210	20	0,15	5071203000
254	-	0,40	175	1,700	10	0,10	5071254000
305	-	0,40	210	2,130	10	0,07	5071305000
350	-	0,40	245	2,500	10	0,06	5071350000
407	-	0,40	280	3,150	10	0,05	5071407000
508	-	0,40	400	4,150	10	0,04	5075080000

Further diameters upon request.

State: 19.04.2024