

KA-GH-PU

Double-walled, flexible polyurethane hose

- dental technology
- medical technology

MEDIUM



PROPERTIES



Structure:

Double walled, flexible polyurethane hose, inside and outside smooth, with rigid PVC helix and a hollow chamber running parallel to the helix

Applications:

Special hose for dental and medical appliances

Temperature range:

-5°C to + 60°C

Colour:

light-grey, other colours on request

I.D. Ø mm	O.D. Ø mm	Wall thickness mm	r (mind.) mm	Weight ca. kg/m	Vacuum mbar	Pressure bar	Part no.
8	12	2,0	10	0,080	300	-	2-8808-008-00
11	15	2,0	13	0,090	290	-	2-8808-011-00
12	16	2,0	13	0,090	280	-	2-8808-012-00
13	17	2,0	13	0,090	280	-	2-8808-013-00
15	19	2,0	13	0,100	270	-	2-8808-015-00
16	20	2,0	20	0,120	260	-	2-8808-016-00
17	21	2,0	21	0,130	250	-	2-8808-017-00
20	25	2,5	21	0,140	230	-	2-8808-020-00
22	27	2,5	23	0,150	230	-	2-8808-022-00
25	30	2,5	23	0,190	200	-	2-8808-025-00
32	37	2,5	30	0,220	150	-	2-8808-032-00

Further diameters upon request.

State: 19.04.2024

VACUFLEX GmbH | Hessenring 8-12
64546 Mörfelden-Walldorf | Germany
Tel. +49 6105 9339 0 | Fax: +49 6105 9339 60
info@vacuflex.de | www.vacuflex.de

All technical data, measured at 23°C, are general orientation values and are subject to production-related tolerances. Max. operating pressures apply only for short periods. We reserve the right to make technical changes and color deviations. Other versions are available upon request.
Stand: 04/2024