

KD-PVC STRETCH

Highly flexible PVC hose with
spring steel helix

- highly flexible
- can be extended two or three times its normal length
- returns to normal length when released



MEDIUM



PROPERTIES



Structure:

Soft PVC, Shore A70 outer wall; PVC-coated spring steel spiral welded to the outer wall

Characteristics:

Highly flexible hose that can be extended two or three times its normal length, it returns to normal length when released, Spiral pitch left-hand

Applications:

Household vacuum cleaners, industrial extractor equipment, dust and fume extraction, medical technology and driers etc.

Temperature range:

-10°C to +70°C

Colour:

Black, other colours on request

I.D. Ø mm	O.D. Ø mm	Wall thickness mm	r (mind.) mm	Weight ca. kg/m	Vacuum mbar	Pressure bar	Part no.
25	30	-	25	0,430	550	-	1-7006-025-00
28	33	-	28	0,480	500	-	1-7006-028-00
30	35	-	30	0,510	500	-	1-7006-030-00
32	37	-	32	0,540	500	-	1-7006-032-00
38	43	-	38	0,650	450	-	1-7006-038-00
40	45	-	40	0,910	450	-	1-7006-040-00
44	49	-	55	1,000	450	-	1-7006-044-00
51	56	-	51	1,160	400	-	1-7006-051-00

Further diameters upon request.

State: 29.04.2024

VACUFLEX GmbH | Hessenring 8-12
64546 Mörfelden-Walldorf | Germany
Tel. +49 6105 9339 0 | Fax: +49 6105 9339 60
info@vacuflex.de | www.vacuflex.de

All technical data, measured at 23°C, are general orientation values and are subject to production-related tolerances. Max. operating pressures apply only for short periods. We reserve the right to make technical changes and color deviations. Other versions are available upon request.
Stand: 04/2024