

MG-V-FLEX

Light weight and highly flexible hose of Premium-PVC

- highly flexible
- light
- excellent properties

MEDIUM



PROPERTIES



Structure:

Outer bore of Soft Premium-PVC, reinforced with PVC coated spring steel spiral, welded to outer bore

Characteristics:

Light weight and highly flexible hose, excellent mechanical properties because of special production process, good chemical resistance

Outer ribs structure to increase mechanical strength and to improve abrasion stability. In addition better gliding effect in particular over smooth surfaces (Skiing effect)

Applications:

Cable protection hose, air ducting, suction/blow or transportation hose, especially feasible for high end vacuum cleaners and industrial scrubbers

Temperature range:

-10°C to +70°C

Colour:

Black, other colours on request

Specials:

Cuffs available

I.D. Ø mm	O.D. Ø mm	Wall thickness mm	r (mind.) mm	Weight ca. kg/m	Vacuum mbar	Pressure bar	Part no.
32	36	0,55 ± 0,05	36	0,210	300	0,5	5-9906-032-00
38	43	0,55 ± 0,05	43	0,309	300	0,5	5-9906-038-00
50	56	0,55 ± 0,05	56	0,464	250	0,4	5-9906-050-00

Further diameters upon request.

VACUFLEX GmbH | Hessenring 8-12
64546 Mörfelden-Walldorf | Germany
Tel. +49 6105 9339 0 | Fax: +49 6105 9339 60
info@vacuflex.de | www.vacuflex.de

All technical data, measured at 23°C, are general orientation values and are subject to production-related tolerances. Max. operating pressures apply only for short periods. We reserve the right to make technical changes and color deviations. Other versions are available upon request.
Stand: 04/2024

State: 30.04.2024

VACUFLEX GmbH | Hessenring 8-12
64546 Mörfelden-Walldorf | Germany
Tel. +49 6105 9339 0 | Fax: +49 6105 9339 60
info@vacuflex.de | www.vacuflex.de

All technical data, measured at 23°C, are general orientation values and are subject to production-related tolerances. Max. operating pressures apply only for short periods. We reserve the right to make technical changes and color deviations. Other versions are available upon request.
Stand: 04/2024

