

NEO I

Hose made of 1 ply neoprene coated fiber glass reinforced fabric

- hot air
- flexible
- smooth inner wall

MEDIUM



PROPERTIES



Structure:

Wall made of 1 ply neoprene coated fiber glass reinforced fabric, reinforced with a spring steel wire and with one additional fiber glass cords on the outside

Characteristics:

Tough and flexible hose with good resistance to high temperatures and chemicals
Length: 4 meters, special length on request

Applications:

Channeling of gases, hot and cold air in engines and the automotive industry

Temperature range:

-55°C to +150°C

Colour:

Black

I.D. Ø mm	O.D. Ø mm	Wall thickness mm	r (mind.) mm	Weight ca. kg/m	Vacuum mbar	Pressure bar	Part no.
25	-	-	25	0,125	530	1,7	5010025000
32	-	-	32	0,160	510	1,5	5010032000
38	-	-	38	0,170	500	1,4	5010038000
44	-	-	44	0,200	450	1,3	5010044000
51	-	-	51	0,250	440	1,2	5010051000
63	-	-	63	0,310	400	1,1	5010063000
76	-	-	76	0,420	350	1,0	5010076000
102	-	-	102	0,660	260	0,9	5010102000
152	-	-	152	0,990	140	0,8	5010152000
203	-	-	203	1,320	700	0,5	5010203000
254	-	-	254	1,660	500	0,4	5010254000

I.D. Ø mm	O.D. Ø mm	Wall thickness mm	r (mind.) mm	Weight ca. kg/m	Vacuum mbar	Pressure bar	Part no.
305	-	-	305	2,000	300	0,1	5010305000

Further diameters upon request.

State: 26.05.2024