

FLEX-ANT


Light duty hose for delivery and discharge of liquids

- food grade
- PVC Wall
- PVC helix with copper wire

MEDIUM



PROPERTIES



Structure:

Soft PVC wall, rigid PVC helix, copper wire

Characteristics:

Smooth inside, transparent wall, food quality according to actual EU regulations, good flexibility, copper wire for electrostatic discharge

Applications:

Discharging and suction of granules and dust for industries, agriculture, feeding systems for machineries

Temperature range:

0°C up to +60°C

Colour:

Clear, white helix

I.D. Ø mm	O.D. Ø mm	Wall thickness mm	r (mind.) mm	Weight ca. kg/m	Vacuum mbar	Pressure bar	Part no.
30	36	3,0	125	0,411	0,76	5,0	5135030000
32	38	3,0	130	0,426	0,76	5,0	5135032000
35	42	3,5	150	0,492	0,76	5,0	5135035000
38	45	3,5	160	0,576	0,76	5,0	5135038000
40	47	3,5	180	0,614	0,76	5,0	5135040000
45	53	4,0	210	0,733	0,76	4,0	5135045000
50	58	4,0	230	0,855	0,76	4,0	5135050000
55	63	4,0	250	0,963	0,76	4,0	5135055000
60	69	4,5	270	1,077	0,76	4,0	5135060000
63	72	4,5	280	1,176	0,76	4,0	5135063000
70	79	4,5	300	1,310	0,76	3,0	5135070000

I.D. Ø mm	O.D. Ø mm	Wall thickness mm	r (mind.) mm	Weight ca. kg/m	Vacuum mbar	Pressure bar	Part no.
75	85	5,0	340	1,436	0,76	3,0	5135075000
80	90	5,0	370	1,617	0,76	3,0	5135080000
90	101	5,5	405	1,874	0,76	2,0	5135090000
100	112	6,0	450	2,279	0,76	2,0	5135100000
120	133	6,5	550	2,935	0,70	2,0	5135120000

Further diameters upon request.

State: 18.08.2019