

KA-GH-PVC

Double-walled, flexible soft-PVC hose

- dental technology
- medical technology

MEDIUM



PROPERTIES



Structure:

Double walled flexible soft PVC hose, smooth inside and outside with rigid PVC helix and a hollow chamber running parallel to the helix

Applications:

Special hose for dental and medical appliances

Temperature range:

- 5°C to + 60°C

Colour:

Light-grey, other colours on request

I.D. Ø mm	O.D. Ø mm	Wall thickness mm	r (mind.) mm	Weight ca. kg/m	Vacuum mbar	Pressure bar	Part no.
8	12	2,0	10	0,080	250	-	2-8208-008-00
11	15	2,0	13	0,090	240	-	2-8208-011-00
12	16	2,0	13	0,090	230	-	2-8208-012-00
13	17	2,0	13	0,090	230	-	2-8208-013-00
15	19	2,0	13	0,100	220	-	2-8208-015-00
16	20	2,0	20	0,120	210	-	2-8208-016-00
17	21	2,0	21	0,130	200	-	2-8208-017-00
20	25	2,5	21	0,140	180	-	2-8208-020-00
22	27	2,5	23	0,150	170	-	2-8208-022-00
25	30	2,5	23	0,190	150	-	2-8208-025-00

Further diameters upon request.

State: 18.08.2019

VACUFLEX GmbH | Hessenring 8-12
64546 Mörfelden-Walldorf | Germany
Tel. +49 6105 9339 0 | Fax: +49 6105 9339 60
info@vacuflex.de | www.vacuflex.de

Depending on installation or operating conditions, the vacuum or pressure values may differ from those stated in the table. In doubtful cases, provide a description of the application you have in mind, and we will be pleased to advise you. Alternative sizes and colours, different tolerances etc. can be supplied on request. Technical Data (at 20°C)
Stand: 08/2019

