

PONDFLEX

Flexible profile hose from a modified TPO with integrated cuffs

- flexible hose
- without spiral

MEDIUM



PROPERTIES



Structure:

Flexible corrugated profile hose made from modified TPO and integrated cuffs, without spiral

Characteristics:

Integrated double cuffs, each every 0,5, 1,0 or 1,5 meters - roll length up to 100,5 meters, floating, production in one piece

Applications:

Artificial ponds, solar heating for pools, landscaping, cable protection

Temperature range:

-30°C to +60°C

Colour:

Black, other colours on request

Specials:

Diameter 38 also available with integrated cuffs each every 0,5 meter

I.D. Ø mm	O.D. Ø mm	Wall thickness mm	r (mind.) mm	Weight ca. kg/m	Vacuum mbar	Pressure bar	Part no.
25	28	1,5	60	0,090	400	1,5	5-8106-025-30
32	39	3,5	80	0,170	400	1,5	5-8106-032-30
38	45	3,5	95	0,215	400	1,5	5-8106-038-30

Further diameters upon request.

State: 18.08.2019

VACUFLEX GmbH | Hessenring 8-12
64546 Mörfelden-Walldorf | Germany
Tel. +49 6105 9339 0 | Fax: +49 6105 9339 60
info@vacuflex.de | www.vacuflex.de

Depending on installation or operating conditions, the vacuum or pressure values may differ from those stated in the table. In doubtful cases, provide a description of the application you have in mind, and we will be pleased to advise you. Alternative sizes and colours, different tolerances etc. can be supplied on request. Technical Data (at 20°C)
Stand: 08/2019