

## POOLFLEX

Flexible profile hose from a modified TPO with integrated cuffs

- flexible hose
- without spiral

### MEDIUM



### PROPERTIES



#### Structure:

Flexible corrugated profile hose made from modified TPO and integrated cuffs, without spiral

#### Characteristics:

Integrated double cuffs each every 1,5 meters. Hose with diameter 38 is also available with integrated cuffs each every 0,66 meter and 0,46 meter. Roll length up to 100,5 meters, floating, production in one piece

#### Applications:

Cleaning of swimming pools, filter technology

#### Temperature range:

-30°C up to +60°C

#### Colour:

Blue

For more information about Eco-friendly products and sustainability at VACUFLEX visit our [sustainability page](#)

[Sustainable Products – Made in Germany](#)

I.D. Ø mm	O.D. Ø mm	Wall thickness mm	r (mind.) mm	Weight ca. kg/m	Vacuum mbar	Pressure bar	Part no.
25	28	1,5	60	0,090	400	1,5	5-8021-025-30
32	39	3,5	80	0,170	400	1,5	5-8021-032-30
38	45	3,5	95	0,215	400	1,5	5-8021-038-30

Further diameters upon request.

State: 16.10.2021

VACUFLEX GmbH | Hessenring 8-12  
64546 Mörfelden-Walldorf | Germany  
Tel. +49 6105 9339 0 | Fax: +49 6105 9339 60  
info@vacuflex.de | www.vacuflex.de

Depending on installation or operating conditions, the vacuum or pressure values may differ from those stated in the table. In doubtful cases, provide a description of the application you have in mind, and we will be pleased to advise you. Alternative sizes and colours, different tolerances etc. can be supplied on request. Technical Data (at 20°C)  
Stand: 10/2021

