

## SERIE 3 PUR M IND

Flexible ducting, reinforced  
with rigid antishock PVC  
helix

- light and flexible ducting
- rigid PVC helix

### MEDIUM



### PROPERTIES



#### Structure:

Light weight and very flexible polyurethane ducting, reinforced with rigid PVC helix, flexible ducting made of polyester polyurethane wall, reinforced with rigid antishock PVC helix

#### Characteristics:

Industrial version, good abrasion resistance, very flexible, smooth bore

#### Applications:

Designed for light suction and transport of abrasive particles, granules, waste and dust in plastic, wood, building industries and agriculture

#### Temperature range:

-30°C to +80°C

#### Colour:

Transparent, grey helix

#### Special construction:

[Serie 3 PUR M AL](#): Food grade version

[Serie 3 PUR M AL ANT](#): Food grade and antistatic version

[Serie 3 PUR M IND ANT](#): Industrial and antistatic version

I.D. Ø mm	O.D. Ø mm	Wall thickness mm	r (mind.) mm	Weight ca. kg/m	Vacuum mbar	Pressure bar	Part no.
40	-	0,50	46	0,275	0,20	1,50	
51	-	0,50	59	0,375	0,20	1,00	
60	-	0,50	69	0,500	0,12	1,00	
63	-	0,50	72	0,510	0,16	1,00	
70	-	0,60	81	0,615	0,16	1,00	
76	-	0,60	87	0,710	0,16	1,00	
80	-	0,60	92	0,750	0,16	1,00	

I.D. Ø mm	O.D. Ø mm	Wall thickness mm	r (mind.) mm	Weight ca. kg/m	Vacuum mbar	Pressure bar	Part no.
90	-	0,60	104	0,800	0,14	1,00	
100	-	0,60	115	0,910	0,13	1,00	
102	-	0,60	117	0,910	0,13	0,80	
110	-	0,60	127	0,950	0,12	0,80	
127	-	0,65	146	1,200	0,10	0,80	
203	-	0,70	233	2,330	0,04	0,40	

Further diameters upon request.

State: 18.08.2019