

VC2 PU


An inside absolutely smooth full plastic hose

- highly flexible
- light
- abrasion resistant

MEDIUM



PROPERTIES



Structure:

PU reinforcement spiral embedded in wall, spiral pitch right-hand

Characteristics:

An inside absolutely smooth full plastic hose, also applicable with overpressure, light, highly flexible, resistant to microbes and hydrolysis

Applications:

Protective and transport hose for electrical and household appliances, suction hose for granular materials, special hose for medial applications etc.

Temperature range:

-30°C to +90°C

Colour:

Black, grey oder transparent, other colours on request

I.D. Ø mm	O.D. Ø mm	Wall thickness mm	r (mind.) mm	Weight ca. kg/m	Vacuum mbar	Pressure bar	Part no.
10	-	-	10	0,073	950	3,5	3-6806-010-00
13	-	-	13	0,095	950	3,5	3-6806-013-00
20	-	-	20	0,147	950	3,5	3-6806-020-00
25	-	-	25	0,189	650	2,5	3-6806-025-00
30	-	-	30	0,226	650	2,5	3-6806-030-00
32	-	-	32	0,240	650	2,5	3-6806-032-00
38	-	-	38	0,283	600	2,5	3-6806-038-00
40	-	-	40	0,300	600	2,5	3-6806-040-00
45	-	-	45	0,337	600	2,5	3-6806-045-00
50	-	-	50	0,377	550	2,0	3-6806-050-00
60	-	-	60	0,452	550	2,0	3-6806-060-00

Further diameters upon request.

State: 18.08.2019