

## VSM-POOL

Inside smooth full plastic hose with low flow resistance

- good resilience
- excellent flexibility
- light construction

### MEDIUM



### PROPERTIES



**Structure:**  
Modified TPO

**Characteristics:**  
Inside smooth full plastic hose with low flow resistance, good resilience (crush proofed), floatable and excellent flexibility

**Applications:**  
Cleaning of swimming pools, filter technology

**Temperature range:**  
-50°C up to +60°C

**Colour:**  
Translucent with blue shoulder, other colours on request

**Specials:**  
Screw cuffs available

I.D. Ø mm	O.D. Ø mm	Wall thickness mm	r (mind.) mm	Weight ca. kg/m	Vacuum mbar	Pressure bar	Part no.
32	40,5	-	80	0,221	500	0,50	4-1100-032-01
38	48,0	-	95	0,322	400	0,40	4-1100-038-01
50	61,0	-	120	0,425	250	0,25	4-1100-050-01
51	62,0	-	122	0,435	250	0,25	4-1100-051-01

Further diameters upon request.

State: 18.08.2019

VACUFLEX GmbH | Hessenring 8-12  
64546 Mörfelden-Walldorf | Germany  
Tel. +49 6105 9339 0 | Fax: +49 6105 9339 60  
info@vacuflex.de | www.vacuflex.de

Depending on installation or operating conditions, the vacuum or pressure values may differ from those stated in the table. In doubtful cases, provide a description of the application you have in mind, and we will be pleased to advise you. Alternative sizes and colours, different tolerances etc. can be supplied on request. Technical Data (at 20°C)  
Stand: 08/2019