

## VSM-S01

Very smooth internal profile  
hose made of modified TPO

- highly flexible
- good resilience
- high internal smoothness

### MEDIUM



### PROPERTIES



#### Structure:

Modified TPO

#### Characteristics:

An inside smooth full-plastic profile hose with low flow resistance, good resilience (when compression or bent) with excellent flexibility

#### Applications:

Household and industrial vacuum cleaners

#### Temperature range:

-50°C to + 60°C

#### Colour:

Silver metallic

I.D. Ø mm	O.D. Ø mm	Wall thickness mm	r (mind.) mm	Weight ca. kg/m	Vacuum mbar	Pressure bar	Part no.
25	33,0	-	50	0,110	600	0,60	4-1125-025-00
27	35,5	-	60	0,130	600	0,60	4-1125-027-00
29	38,5	-	65	0,205	600	0,60	4-1125-029-00
32	40,5	-	70	0,275	500	0,50	4-1125-032-00
36	44,7	-	75	0,290	500	0,50	4-1125-036-00
37	45,1	-	80	0,295	500	0,50	4-1125-037-00
38	48,0	-	80	0,320	400	0,40	4-1125-038-00
50	61,0	-	120	0,420	250	0,25	4-1125-050-00

Further diameters upon request.

State: 18.08.2019

VACUFLEX GmbH | Hessenring 8-12  
64546 Mörfelden-Walldorf | Germany  
Tel. +49 6105 9339 0 | Fax: +49 6105 9339 60  
info@vacuflex.de | www.vacuflex.de

Depending on installation or operating conditions, the vacuum or pressure values may differ from those stated in the table. In doubtful cases, provide a description of the application you have in mind, and we will be pleased to advise you. Alternative sizes and colours, different tolerances etc. can be supplied on request. Technical Data (at 20°C)  
Stand: 08/2019

