

VC1 PU

An inside absolutely smooth full plastic hose, soft PU wall

- highly flexible
- light
- abrasion resistant

MEDIUM



PROPERTIES



Structure:

Soft PU Wall, reinforced with a shock resistant PVC spiral, spiral pitch right-hand

Characteristics:

An inside absolutely smooth full plastic hose, also applicable at low pressures, light, highly flexible and abrasion resistant, resistant to microbes and hydrolysis

Applications:

Cable protection and transport hose for machine-building and engineering applications

Temperature range:

-20°C to +60°C

Colour:

Black or grey, other colours on request

I. D. Ø mm	O.D. Ø mm	Wall thickness mm	r(mind.) mm	Weight ca. kg/m	Vacuum mbar	Pressure bar	Part no.
10	-	-	10	0,072	850	2,5	-
13	-	-	13	0,093	850	2,5	-
20	-	-	20	0,144	850	2,5	-
25	-	-	25	0,185	550	2,0	-
30	-	-	30	0,222	550	2,0	-
32	-	-	32	0,236	550	2,0	-
38	-	-	38	0,278	500	1,5	-
40	-	-	40	0,296	500	1,5	-
45	-	-	45	0,330	500	1,5	-
50	-	-	50	0,370	450	1,0	-
60	-	-	60	0,443	450	1,0	-

Further diameters upon request.

State: 04.05.2024