

VACUFLEX®

- [Products](#)
 - [Hoses](#)
 - [Connections](#)
 - [Brochure](#)
- [Company](#)
 - [About us](#)
 - [Sustainability](#)
 - [Code of Conduct](#)
 - [Certificates](#)
- [Service](#)
 - [VACUFLEX® Hose Academy](#)
 - [Dental hoses](#)
- [News](#)
- [Career](#)

- [Deutsch](#)
- [English](#)
- |
- [Chinese](#)

VC1 PU

An inside absolutely smooth full plastic hose, soft PU wall

- highly flexible
- light
- abrasion resistant

MEDIUM



PROPERTIES



Structure:

Soft PU Wall, reinforced with a shock resistant PVC spiral, spiral pitch right-hand

Characteristics:

An inside absolutely smooth full plastic hose, also applicable at low pressures, light, highly flexible and abrasion resistant, resistant to microbes and hydrolysis

Applications:

Cable protection and transport hose for machine-building and engineering applications

Temperature range:

-20°C to +60°C

Colour:

Black or grey, other colours on request

I. D. Ø mm	O.D. Ø mm	Wall thickness mm	r(mind.) mm	Weight ca. kg/m	Vacuum mbar	Pressure bar	Part no.
10	-	-	10	0,072	850	2,5	-
13	-	-	13	0,093	850	2,5	-
20	-	-	20	0,144	850	2,5	-
25	-	-	25	0,185	550	2,0	-
30	-	-	30	0,222	550	2,0	-
32	-	-	32	0,236	550	2,0	-
38	-	-	38	0,278	500	1,5	-
40	-	-	40	0,296	500	1,5	-
45	-	-	45	0,330	500	1,5	-
50	-	-	50	0,370	450	1,0	-
60	-	-	60	0,443	450	1,0	-

Further diameters upon request.

State: 30.11.2022

Contact

VACUFLEX GmbH
Hessenring 8 -12
64546 Mörfelden-Walldorf
Germany

T +49 6105 9339 0
F +49 6105 9339 60
info@vacuflex.de

[Imprint](#)
[Data privacy](#)
[Terms of Use](#)

VACUFLEX GmbH | Hessenring 8-12
64546 Mörfelden-Walldorf | Germany
Tel. +49 6105 9339 0 | Fax: +49 6105 9339 60
info@vacuflex.de | www.vacuflex.de

Depending on installation or operating conditions, the vacuum or pressure values may differ from those stated in the table. In doubtful cases, provide a description of the application you have in mind, and we will be pleased to advise you. Alternative sizes and colours, different tolerances etc. can be supplied on request. Technical Data (at 20°C)
Stand: 11/2022






VACUFLEX GmbH | Hessenring 8-12
64546 Mörfelden-Walldorf | Germany
Tel. +49 6105 9339 0 | Fax: +49 6105 9339 60
info@vacuflex.de | www.vacuflex.de

Depending on installation or operating conditions, the vacuum or pressure values may differ from those stated in the table. In doubtful cases, provide a description of the application you have in mind, and we will be pleased to advise you. Alternative sizes and colours, different tolerances etc. can be supplied on request. Technical Data (at 20°C)
Stand: 11/2022







•
VACUFLEX Advanced Hoses Ltd.

Room 101 of F Building No.2,
Xingye Road, Jiuwangmiao Village,
Zip code 511458, Nansha District,
Guangzhou, China

T +86 20 846 852 37

F +86 20 390 053 10

info@vacuflex.cn

www.vacuflex.cn

Changxing VACUFLEX Hose Technology Co., Ltd

Sino-German International Industrial Zone,
Changxing Economic and Technological
Development Zone,
Zip code 313100, Changxing, Huzhou City,
Zhejiang Province, China

T +86 572 6666208

M +86 135 6025 2608

F +86 572 6666207

info@vacuflex.cn

www.vacuflex.cn

VACUFLEX GmbH | Hessenring 8-12
64546 Mörfelden-Walldorf | Germany
Tel. +49 6105 9339 0 | Fax: +49 6105 9339 60
info@vacuflex.de | www.vacuflex.de

Depending on installation or operating conditions, the vacuum or pressure values may differ from those stated in the table. In doubtful cases, provide a description of the application you have in mind, and we will be pleased to advise you. Alternative sizes and colours, different tolerances etc. can be supplied on request. Technical Data (at 20°C)
Stand: 11/2022







Management
System
ISO 9001:2015

www.tuv.com
ID 9000009721

 SCHAUBURG HOSE TECHNOLOGY GROUP

© 2022 VACUFLEX GmbH

- [Products](#)
 - [Hoses](#)
 - [Connections](#)
 - [Brochure](#)
- [Company](#)
 - [About us](#)
 - [Sustainability](#)
 - [Code of Conduct](#)
 - [Certificates](#)
- [Service](#)
 - [VACUFLEX® Hose Academy](#)
 - [Dental hoses](#)
- [News](#)
- [Career](#)
- [Imprint](#)
- [Data privacy](#)
- [Terms of Use](#)
- [404](#)
-  [de](#)
-  [en](#)
- [CN](#)



VACUFLEX GmbH | Hessenring 8-12
64546 Mörfelden-Walldorf | Germany
Tel. +49 6105 9339 0 | Fax: +49 6105 9339 60
info@vacuflex.de | www.vacuflex.de

Depending on installation or operating conditions, the vacuum or pressure values may differ from those stated in the table. In doubtful cases, provide a description of the application you have in mind, and we will be pleased to advise you. Alternative sizes and colours, different tolerances etc. can be supplied on request. Technical Data (at 20°C)
Stand: 11/2022