

VSM-A

**Very smooth internal profile
hose made of antistatic
modified TPO**

- highly flexible
- good resilience
- high internal smoothness

MEDIUM



PROPERTIES



Structure:

Modified TPO

Characteristics:

An inside, smooth full-plastic profile hose with low flow resistance, good resilience (when compressed or bent) and excellent flexibility; surface resistance according to DIN 53482 $\leq 10^{10} \Omega/m$ (Ohm/Meter)

Applications:

Industrial vacuum cleaners, textile machines, woodworking machines, granulate conveyors and engineering

Temperature range:

-50 °C to + 60 °C

Colour:

Black

I.D. Ø mm	O.D. Ø mm	Wall thickness mm	r (mind.) mm	Weight ca. kg/m	Vacuum mbar	Pressure bar	Part no.
25	33	-	50	0,250	600	0,60	4-1806-025-00
27	35,5	-	60	0,280	600	0,60	4-1806-027-00
32	40,5	-	70	0,320	500	0,50	4-1806-032-00
35	43,6	-	75	0,360	500	0,50	4-1806-035-00
38	48,0	-	80	0,380	400	0,40	4-1806-038-00
40	50,0	-	90	0,420	400	0,40	4-1806-040-00
45	55,0	-	100	0,460	300	0,30	4-1806-045-00
48	58,0	-	110	0,490	280	0,28	4-1806-048-00
50	61,0	-	120	0,510	250	0,25	4-1806-050-00
60	72,0	-	140	0,620	200	0,20	4-1806-060-00

I.D. Ø mm	O.D. Ø mm	Wall thickness mm	r (mind.) mm	Weight ca. kg/m	Vacuum mbar	Pressure bar	Part no.
63	74,0	-	150	0,660	180	0,18	4-1806-063-00
70	81,0	-	165	0,730	170	0,17	4-1806-070-00
75	87,0	-	180	0,750	160	0,16	4-1806-075-00
80	92,0	-	200	0,810	150	0,15	4-1806-080-00

Further diameters upon request.

State: 26.04.2024