

VSM-L-S02

Inside smooth full plastic hose with low flow resistance

- good resilience
- excellent flexibility
- very light construction

MEDIUM



PROPERTIES



Structure:

Modified TPO

Characteristics:

Inside smooth full plastic hose with low flow resistance, good resilience (crush proofed) and excellent flexibility

Applications:

Industrial vacuum cleaners, professional vacuum cleaners and cable protection hoses

Temperature range:

-50°C up to +60°C

Colour:

Black

Specials:

Also with coloured protection shoulder available and a wide range of connection parts

For more information about Eco-friendly products and sustainability at VACUFLEX visit our sustainability page

[Sustainable Products – Made in Germany](#)

I.D. Ø mm	O.D. Ø mm	Wall thickness mm	r (mind.) mm	Weight ca. kg/m	Vacuum mbar	Pressure bar	Part no.
27	34	-	45	0,155	500	0,50	4-2206-027-00
29	36	-	45	0,165	500	0,50	4-2206-029-00
32	39	-	50	0,185	450	0,45	4-2206-032-00
38	45	-	55	0,240	350	0,35	4-2206-038-00
50	58	-	75	0,350	200	0,20	4-2206-050-00

Weitere Durchmesser auf Anfrage.

VACUFLEX GmbH | Hessenring 8-12
64546 Mörfelden-Walldorf | Germany
Tel. +49 6105 9339 0 | Fax: +49 6105 9339 60
info@vacuflex.de | www.vacuflex.de

All technical data, measured at 23°C, are general orientation values and are subject to production-related tolerances. Max. operating pressures apply only for short periods. We reserve the right to make technical changes and color deviations. Other versions are available upon request.
Stand: 09/2024

State: 17.09.2024

VACUFLEX GmbH | Hessenring 8-12
64546 Mörfelden-Walldorf | Germany
Tel. +49 6105 9339 0 | Fax: +49 6105 9339 60
info@vacuflex.de | www.vacuflex.de

All technical data, measured at 23°C, are general orientation values and are subject to production-related tolerances. Max. operating pressures apply only for short periods. We reserve the right to make technical changes and color deviations. Other versions are available upon request.
Stand: 09/2024

